

P/N NAS1790-3R5

Military-Fasteners.com

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS17903R5
Minimum Qty (MOQ):	80 EA
NSN:	5305-01-495-0587
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS1790-3R5 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.288 Inches Nominal
Fastener Length:	0.6255 Inches Minimum And 0.6755 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.339 Inches Minimum
Head Height:	0.015 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.3025 Inches Minimum And 0.3225 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS1790-3R5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.