

Description

Fastener Length: 11/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17903R6
Minimum Qty (MOQ):	95 EA
NSN:	5305-01-576-3722
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1790-3R6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.713 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.189 Nominal Inches
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	Nimrod Mra4; Nimrod 2000; Air Reconnaissance
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.375 Nominal Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 10o Degree Flush Head, 160,000 Psi Uts
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626, Uts G41400 Mil Spec Single Material Response Overall Or Ams6415, E4340 (uts G43400) Assn Std Single Material Response Overall Or Mil-s-5000, Uts G43406 Mil Spec Single Material Response Overall Or Mil-s-6049, Uts G87400 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1790-3R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.