

Description

Fastener Length: 17/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS17903R7
Minimum Qty (MOQ):	75 EA
NSN:	5306-01-572-8984
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1790-3R7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.515 Inches Minimum And 0.535 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Degree Flush Head 160,000 Psi Uts
Material:	Steel Comp 4140 Overall And Steel Comp 4340 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall And Ams6415 Assn Std 2nd Material Response Overall And Mil-s-60494 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li. Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1790-3R7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.