

Description

Fastener Length: 27/32", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS17903R8       |
| Minimum Qty (MOQ): | 100 EA           |
| NSN:               | 5306-01-575-9074 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N NAS1790-3R8 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.338 Inches Nominal  |
| <b>Fastener Length:</b>                               | 0.823 Inches Minimum And 0.853 Inches Maximum   |
| <b>Head Style:</b>                                    | Fillister Countersunk   |
| <b>Head Diameter:</b>                                 | 0.339 Inches Minimum And 0.381 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.083 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.189 Inches Nominal  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.485 Inches Minimum And 0.515 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams 6415 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1790-3R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.