

Description

Fastener Length: 17/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1790C3R3
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-575-9061
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS1790C3R3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.510 Inches Minimum And 0.540 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Head Height:	0.083 Inches Nominal
Grip Diameter:	0.189 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.172 Inches Minimum And 0.202 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams5853 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1790C3R3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.