

P/N NAS1791A3-3

Military-Fasteners.com

#### Description

Self-Locking Nutplate part number

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1791A33
Minimum Qty (MOQ):	10
NSN:	5310-01-090-1544
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1791A3-3 Specifications

Thread Class:3bThread Direction:Right-handLocking Feature:Prevailing Torque All Metal DesignCounterbore Diameter:0.194 Inches Minimum NutLubrication:Ory Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches Maximum
Locking Feature:Prevailing Torque All Metal DesignCounterbore Diameter:0.194 Inches Minimum NutLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum
Counterbore Diameter:0.194 Inches Minimum NutLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum
Mounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum
Mounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum
Nut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum
Nut Length:0.948 Inches MaximumNut Height:0.375 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum
Plate Thickness: 0.027 Inches Minimum And 0.037 Inches Maximum   Plate Width: 0.445 Inches Maximum
Plate Width: 0.445 Inches Maximum
Removable Nut Manufacturer Code: 80205
Nut Counterbore Depth: 0.188 Inches Minimum Nut
Nut Mounting Provision: Straight Holes
Mounting Hole Arrangement Style: 2 Holes
Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum
Removable Nut Manufacturer Part Number: Nas1794a3-3
Thread Series: Unjf
Features Provided: Floating Nut
Thread Quantity Per Inch: 32
Nominal Thread Size: 0.190 Inches
Material: Steel Nut
Material: Steel Shell
Surface Treatment: Cadmium Nut And Chromate Nut
Surface Treatment: Cadmium Shell And Chromate Shell
Surface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Shell
Surface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Nut
Specification/standard Data: 80205-nas1791 Professional/industrial Association Standard

## How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A3-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.