

**Description**

Thread Size: 3/16", Nut Length: 15/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1791A34
Minimum Qty (MOQ):	10
NSN:	5310-00-093-3299
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics



# P/N NAS1791A3-4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Plate Width:	0.454 Inches Maximum
Removable Nut Manufacturer Code:	76301
Nut Counterbore Depth:	0.250 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.344 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.688 Inches Nominal
Removable Nut Manufacturer Part Number:	St3m445a3m4
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	Clip Material,cres And Clip Surface Treatment,passivated
Material:	Steel Base
Material:	Steel Nut
Surface Treatment:	Cadmium Base
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Base
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut

## How to Order



Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1791A3-4](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791A3-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.