

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1791A36
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-108-4445
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1791A3-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Nominal Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.562 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Plate Width:	0.445 Inches Maximum
Removable Nut Manufacturer Code:	80205
Nut Counterbore Depth:	0.375 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Removable Nut Manufacturer Part Number:	Nas1794a3-6
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Nut
Material:	Steel Shell
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Shell And Chromate Shell
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Shell
Specification/standard Data:	80205-nas1791 Professional/industrial Association Standard

How to Order

Order this plate - two lug locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791A3-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.