

# P/N NAS1791A4-2

## **Description**

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS1791A42

Minimum Qty (MOQ): 10

NSN: 5310-01-090-1543

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1791A4-2 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.357 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Plate Width:	0.547 Inches Maximum
Removable Nut Manufacturer Code:	80205
Nut Counterbore Depth:	0.125 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Removable Nut Manufacturer Part Number:	Nas1794a4-2
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Nut
Material:	Steel Shell
Surface Treatment:	Cadmium Nut And Chromate Nut
Surface Treatment:	Cadmium Shell And Chromate Shell
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Shell
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Nut
Specification/standard Data:	80205-nas1791 Professional/industrial Association Standard

# Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791A4-2</a> and selecting the your cart you can check you can check you can check you can check you can che