

## Description

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1791A46
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-283-7522
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1791A4-6 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.254 Inches Minimum Nut
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	1.292 Inches Maximum
<b>Nut Height:</b>	0.600 Inches Maximum
<b>Plate Thickness:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Plate Width:</b>	0.574 Inches Nominal
<b>Nut Counterbore Depth:</b>	0.375 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.495 Inches Minimum And 0.505 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.998 Inches Minimum And 1.002 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Iron Alloy 660 Shell
<b>Material Document And Classification:</b>	Ams5525 Assn Std 1st Material Response Shell Or Ams5735 Assn Std 2nd Material Response Shell
<b>Surface Treatment:</b>	Passivate Shell
<b>Specification/standard Data:</b>	76301-st3-443 Manufacturers Standard

## How to Order

Order this plate - two lug locknut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1791A4-6](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791A4-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.