

Description

Thread Size: 13/64", Nut Length: 61/64", Nut Height: 15/64", floating, two lug, NAS1791 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1OAX86A307R11](#)

SKU / Model:	NAS1791C31
Minimum Qty (MOQ):	20
NSN:	5310-00-379-4633
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1791C3-1 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.220 Inches Maximum
Plate Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Plate Width:	0.474 Inches Nominal
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Shell
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell Or Ams 5735 Assn Std Single Material Response Shell
Surface Treatment:	Passivate Shell
Specification/standard Data:	76301-st3-443 Manufacturers Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C3-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.