

Description

Thread: 10-32, Nut Length: 15/16", Nut Height: 9/32", two lug, NAS1791 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1OAX86A307R12](#)

SKU / Model:	NAS1791C32
Minimum Qty (MOQ):	10
NSN:	5310-00-143-0358
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1791C3-2 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut And 0.207 Inches Maximum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.093 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.296 Inches Nominal
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.440 Inches Nominal
Nut Counterbore Depth:	0.100 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	Plate U Shpae 0.220 In. High,one Hole Each Side To Hold Retaining Clip
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C3-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.