

P/N NAS1791C3-2NP

Military-Fasteners.com

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 19/64

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1791C32NP
Minimum Qty (MOQ):	10
NSN:	5310-01-331-6292
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1791C3-2NP Specifications

Locking Feature: Pervaling Torque All Metal Design Counterbore Diameter: 0.194 Inches Moximum Mounting Hole Diameter: 0.194 Inches Maximum Nut Style: Plate (Indating) Nut Length: 0.948 Inches Maximum Nut Height: 0.312 Inches Maximum Plate Thickness: 0.397 Inches Maximum Plate Width: 0.484 Inches Maximum Nut Gounterbore Depth: 0.125 Inches Maximum Nut Gounterbore Depth: 0.125 Inches Maximum Nut Gounter Provision: Stralght Holes Mounting Hole Arrangement Style: 1.019 Inches Maximum Obletance From Aperture Center To Mounting Hole .100 Inches Minimum Center: 0.100 Inches Minimum Center: 0.900 Inches Minimum Strades From Aperture Center To Mounting Hole .900 Inches Minimum Nong Length: 0.000 Deg Fahrenheit Nominal Thread Quantity Per Inch: 32 Nominal Thread Steres: 0.100 Inches Material: Iron Alloy 651 Nut Material: Iron Alloy 651 Nut Material Document And Classification: Ams5525 Assn	Thread Class:	3b
Counterbore Diameter:0.194 Inches Nominal NutMounting Hole Diameter:0.103 Inches MaximumNut Style:0.496 Inches MaximumNut Length:0.496 Inches MaximumNut Height:0.312 Inches MaximumPlate Hilde:0.332 Inches MaximumPlate Hilde:0.332 Inches MaximumNut Counterbore Depth:0.332 Inches Maximum NutNut Counterbore Depth:0.325 Inches Maximum NutNut Counterbore Depth:0.125 Inches MaximumNut Counterbore Depth:0.125 Inches Minimum NutDistance From Aperture Center To Mounting Hole2 HolesCenter:0.100 Inches MinimumConter Conter Distance Between Mounting Hole0.000 Eng Anirenheit NominalConter Scherer Distance Between Mounting Hole900 Inches MaximumTirread Quantity Per Inch:0.100 Inches MinimumTirread Series:0.100 Inches MinimumNominal Thread Size:0.100 Inches MinimumMaterial:Incol Nord SchellMaterial:Incol Nord SchellMaterial:Incol Nord SchellMaterial:Nord SchellMaterial:Incol Nord SchellMaterial:Nord Schell Material Response Nut Or Ams5732 Assn Sch Single Mater	Thread Direction:	Right-hand
Mounting Hole Diameter:0.103 Inches MaximumNut Esptie:Plate (floating)Nut Length:0.948 Inches MaximumNut Helght:0.312 Inches MaximumPlate Thickness:0.307 Inches MaximumPlate Thickness:0.307 Inches MaximumNut Guointerbore Depth:0.484 Inches Maximum NutNut Mounting Provision:Straight HolesMut Guointerbore Depth:0.100 Inches Minimum NutConter Fore Agerture Center To Mounting HoleStraight HolesMounting Hole Arrangement Style:0.690 Inches MinimumCenter:0.500 Inches MaximumCenter:0.500 Inches MaximumCenter:0.500 Inches MaximumCenter:0.500 Inches MaximumAlong Engrhe:0.500 Inches MaximumAlong Engrhe:0.500 Inches MaximumThread Sterie:0.100 Inches MaximumMaterial:0.100 Inches MaximumMaterial:0.100 Inches MaximumMaterial:0.100 Inches MaximumMaterial:0.100 Inches MaximumMaterial:0.100 Inches MaximumMaterial:0.100 Inches StallMaterial:0.100 Inches Staller Material Response Nut Orams5732 Assn Std Single Material Response Nut Orams5732 Assn S	Locking Feature:	Prevailing Torque All Metal Design
Nut Style:Plate (floating)Nut Legth:0.948 Inches MaximumNut Height:0.037 Inches MaximumNut Height:0.037 Inches MaximumPlate Thickness:0.037 Inches MaximumPlate Thickness:0.132 Inches Maximum NutNut Gounterbore Depth:0.125 Inches Minimum NutNut Mounting Provision:0.125 Inches Minimum NutNut Mounting Provision:2 HolesDistance From Aperture Center To Mounting Hole Center:0.100 Inches MinimumCenter To Center Distance Between Mounting Hole Center:0.900 Inches MaximumCenter To Center Distance Between Mounting Hole Center:0.900 Inches MaximumThread Series:0.100 Inches MaximumMonting Hole Staries:0.900 Inches MaximumThread Series:0.910 InchesNominal Thread Size:0.910 InchesMaterial:Iron Alloy G51 MutMaterial:Iron Alloy G51 ShellMaterial:Iron Alloy G51 ShellMaterial Document And Classification:AmS525 Assn Std Single Material Response Nut Or AmS732 Assn Std Single Material Response NutMaterial Document And Classification:AmS525 Assn Std Single Material Response NutSurface Treatment:AmS688 Assn Std Single Material Response ShellSurface Treatment:Basivat ShellSurface Treatment:Basivat Shell	Counterbore Diameter:	0.194 Inches Nominal Nut
Nut Length:0.948 Inches MaximumNut Height:0.312 Inches MaximumPlate Hilckness:0.307 Inches MaximumPlate Wilch:0.484 Inches MaximumNut Counterbore Depth:0.125 Inches Minimum NutNut Gunterbore Depth:0.125 Inches Minimum NutNut Mounting Provision:Xielgit HolesDistance From Aperture Center Downting Hole200 Inches MinimumDistance From Aperture Center Downting Hole0.00 Inches MinimumCenter Dotante Between Mounting Hole0.00 Inches MaximumThread Series:0.00 Ioge Fahrenheit NominalThread Quantity Per Inch:0.00 Ioge Fahrenheit NominalMaterial:100 Inches StatueMaterial:100 Inches StatueMaterial:<	Mounting Hole Diameter:	0.103 Inches Maximum
Nu Height:0.312 Inches MaximumPlate Thickness:0.037 Inches MaximumPlate Thickness:0.037 Inches MaximumPlate Width:0.484 Inches MaximumNut Gounterbore Depth:0.125 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hoe Arrangement Style:1.406Center To Center Distance Between Mounting Hoe.100 Inches MinimumCenter To Center Distance Between Mounting Hoe.000 Inches MaximumCenter To Center Distance Between Mounting Hoe.000 Deg Fahrenheit NominalTemp Asting:0.000 Deg Fahrenheit NominalThread Series:0.190 InchesMounting Hoed Size:0.190 InchesMaterial:Inon Alloy 651 NutMaterial:Inon Alloy 651 NutMaterial:Inon Alloy 651 ShellMaterial:Sass Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams573 Assn Std Single Material Response ShellMaterial Document And Classification:Misro Nut Or Ams500	Nut Style:	Plate (floating)
Plate Thickness:0.037 Inches MaximumPlate Width:0.484 Inches MaximumPlate Width:0.484 Inches Maximum NutNut Counterbore Depth:0.125 Inches Minimum NutNut Mounting Provision:Straight HolesMunting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole0.100 Inches MinimumCenter To Center Distance Between Mounting0.000 Inches MinimumCenter To Center Distance Between Mounting Hole0.000 Deg Fahrenheit NominalConter Addition Straight800.00 Deg Fahrenheit NominalToread Series:0.100 InchesMominal Thread Size:0.190 InchesNominal Thread Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Roms525 Assen Std Single Material Response Nut Or Ams5732 Assen Std Single Mater	Nut Length:	0.948 Inches Maximum
Plate Width:0.484 Inches MaximumNut Counterbore Depth:0.125 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Mole Arrangement Style:2 HolesDistance From Aperture Center:0.100 Inches MinimumCenter To Center Distance Between Mounting Holeo.900 Inches MaximumAlong Length:0.900 Inches MaximumAlong Length:0.00 Deg Fahrenheit NominalThread Series:0.00 Deg Fahrenheit NominalNominal Thread Size:0.190 InchesMaterial:0.190 Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams573 Assn Std Single Material Response StellMaterial Document	Nut Height:	0.312 Inches Maximum
Nut Counterbore Depth:0.125 Inches Minimun NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center:o.100 Inches MinimumCenter: To Center Distance Between Mounting Hole Along Length:o.900 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Series:0.100 Inches StatusMaterial:Inches StatusMaterial:Inches StatusMaterial:Inches StatusMaterial:Steel Comp 302 ClipMaterial:Steel Comp 302 ClipMaterial:Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response StellMaterial Document And Classification:Ma5525 Assn Std Single Material Response StellMaterial Document And Classification:Silver NutSurface Treatment:Biver NutSurface Treatment:Pasivate Silver	Plate Thickness:	0.037 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.100 Inches MinimumCenter Distance Between Mounting Hole Along Length:0.690 Inches MaximumCenter Distance Between Mounting Hole Along Length:0.690 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Nominal Thread Size:0.190 Inches 51 NutMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellSurface Treatment:Pasivate ClipSurface Treatment:Pasivate Shell	Plate Width:	0.484 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.100 Inches MinimumCenter To Center Distance Between Mounting Holes Along Length:0.690 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Stel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5688 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Pasivate Clip	Nut Counterbore Depth:	0.125 Inches Minimum Nut
Distance From Aperture Center To Mounting Hole Center:0.100 Inches MinimumCenter To Center Distance Between Mounting Holes Along Length:0.690 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.690 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Size:0.190 InchesMaterial Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Pasivate ClipSurface Treatment:Pasivate Shell	Nut Mounting Provision:	Straight Holes
Center:0.100 inches MinimumCenter To Center Distance Between Mounting Holes Along Length:0.690 Inches MaximumAlong Length:0.690 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 NutMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5252 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5733 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5733 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5733 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5733 Assn Std Single Material Response Nut Or Ams5733 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response Nut Or Ams5733 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Passivate ClipSurface Treatment:Passivate Shell	Mounting Hole Arrangement Style:	2 Holes
Along Length:0.000 Incres MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Passivate ClipSurface Treatment:Passivate Shell	Distance From Aperture Center To Mounting Hole Center:	0.100 Inches Minimum
Thread Series:UnjfThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response NutSurface Treatment:Silver NutSurface Treatment:Passivate ClipSurface Treatment:Passivate Shell	Center To Center Distance Between Mounting Holes Along Length:	0.690 Inches Maximum
Thread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:iron Alloy 651 NutMaterial:iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Pasivate ClipSurface Treatment:Pasivate Shell	Temp Rating:	800.0 Deg Fahrenheit Nominal
Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 651 NutMaterial:Iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Pasivate ClipSurface Treatment:Pasivate Shell	Thread Series:	Unjf
Material:ion Alloy 651 NutMaterial:ion Alloy 651 ShellMaterial:ion Alloy 651 ShellMaterial Document And Classification:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Pasivate ClipSurface Treatment:Pasivate ClipSurface Treatment:Pasivate Shell	Thread Quantity Per Inch:	32
Material:Iron Alloy 651 ShellMaterial:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Pasivate ClipBaterial Document And Classification:Pasivate ClipSurface Treatment:Pasivate Shell	Nominal Thread Size:	0.190 Inches
Material:Steel Comp 302 ClipMaterial Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Passivate ClipBasivate ShellPassivate Shell	Material:	Iron Alloy 651 Nut
Material Document And Classification:Ams5525 Assn Std Single Material Response Nut Or Ams5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Passivate ClipSurface Treatment:Passivate ShellSurface Treatment:Passivate Shell	Material:	Iron Alloy 651 Shell
Material Document And Classification:Assn Std Single Material Response NutMaterial Document And Classification:Ams5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Passivate ClipSurface Treatment:Passivate ShellSurface Treatment:Passivate Shell	Material:	Steel Comp 302 Clip
Material Document And Classification:Ams5688 Assn Std Single Material Response ClipSurface Treatment:Silver NutSurface Treatment:Passivate ClipSurface Treatment:Passivate Shell	Material Document And Classification:	
Surface Treatment: Silver Nut Surface Treatment: Passivate Clip Surface Treatment: Passivate Shell	Material Document And Classification:	Ams5525 Assn Std Single Material Response Shell
Surface Treatment: Passivate Clip Surface Treatment: Passivate Shell	Material Document And Classification:	Ams5688 Assn Std Single Material Response Clip
Surface Treatment: Passivate Shell	Surface Treatment:	Silver Nut
	Surface Treatment:	Passivate Clip
Surface Treatment Document And Classification: Ams2410 Assn Std Single Treatment Response Nut	Surface Treatment:	Passivate Shell
	Surface Treatment Document And Classification:	Ams2410 Assn Std Single Treatment Response Nut

Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Clip
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Shell
Specification/standard Data:	80205-nas1791 Professional/industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C3-2NP</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.