

# P/N NAS1791C3-3K

## **Description**

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS1791C33K

Minimum Qty (MOQ): 5 EA

NSN: 5310-01-342-7249

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1791C3-3K Specifications

Thursd Class	
Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Nominal Nut
Mounting Hole Diameter:	0.103 Inches Maximum
Nut Style:	Plate (floating)
Nut Length:	0.948 Inches Maximum
Nut Height:	0.375 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Plate Width:	0.484 Inches Maximum
Nut Counterbore Depth:	0.188 Inches Nominal Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Special Features:	Dimpled Rivet Holes
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material:	Steel Comp 321 Clip
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Material Document And Classification:	Ams 5688 Assn Std Single Material Response Clip
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1791 Professional/industrial Association Standard

# How to Order Order this plate - two lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C3-3K</a> and selecting the part of the