

P/N NAS1791C3-4

Military-Fasteners.com

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 7/16", floating

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1791C34
Minimum Qty (MOQ):	5
NSN:	5310-01-328-2043
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1791C3-4 Specifications

Pread Direction:Night-hadLocking Feature:Pervailing Torque All Aclas DesignCouncteroor Dismeter:0.91 Inches Annial NutLubrication:0.92 Inches Minium And 0.103 Inches MaximumMust Ighe Diameter:0.93 Inches Mainum And 0.103 Inches MaximumNut Skyie:0.948 Inches MaximumNut Length:0.948 Inches MaximumNut Length:0.948 Inches MaximumNut Length:0.948 Inches MaximumNut Length:0.451 Inches MaximumNut Length:0.451 Inches MaximumNut Length:0.451 Inches MaximumRemosibe Nut Mandraturer Code:0.805 Inches MaximumNut Counterboor Dept:0.250 Inches MaximumNut Counterboor Dept:0.250 Inches MaximumNut Bender Streige:0.331 Inches MaximumNut Bender Streige:0.331 Inches MaximumStreige:0.331 Inches MaximumRemosibe Nut Mandraturer Port Nuther:0.450 Inches MaximumStreige:0.500 Enger Inches MaximumStreige:0.500 Enger Inches MaximumRemosibe:0.500 Enger	Thread Class:	3b
Counterbore Diameter:0.194 Inches Nominal NutLubrication:Dry Flin LubricantMounting Hole Diameter:0.098 Inches Minimu And 0.103 Inches MaximumNut Style:PlatNut Length:0.498 Inches MaximumNut Height:0.498 Inches MaximumNut Height:0.408 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumRemovable Nut Manufacturer Code:0.027 Inches Minimum And 0.037 Inches MaximumNut Gunterbore Depth:0.027 Inches Minimum And 0.037 Inches MaximumNut Mounting Provision:Stolaches Minimum And 0.037 Inches MaximumMounting Provision:Stolaches Minimum And 0.349 Inches MaximumRemovable Nut Manufacturer Path Numere:Nationes MaximumRemovable Nut Manufacturer Path Numere:Nationes MaximumRemovable Nut Manufacturer Path Numere:Nationes MaximumStolace Strone Deptin:0.500 Inches MaximumThread Series:Nationes MaximumRemovable Nut Manufacturer Path Numere:Nationes MaximumThread Series:Nationes MaximumThread Series:Nationes MaximumRemovable Nut Manufacture:Nationes MaximumNationes Maximum <td< th=""><th>Thread Direction:</th><th>Right-hand</th></td<>	Thread Direction:	Right-hand
Lubrication:Dyr Film LubricantMouting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Lengte:PlateNut Length:0.498 Inches MaximumNut Height:0.498 Inches MaximumNut Height:0.498 Inches MaximumPlate Width:0.027 Inches Minimum And 0.037 Inches MaximumRemovable Nut Manufacturer Code:0.027 Inches Minimum And 0.037 Inches MaximumRemovable Nut Manufacturer Code:0.027 Inches Minimum And 0.037 Inches MaximumNut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Straight HolesNut Mounting Hole Arrangement Style:1.406Distance From Aperture Center To Mounting Hole3.39 Inches Minimum And 0.349 Inches MaximumCenter Distance Between Mounting HoleAssi 1942.4Removable Nut Manufacturer Part Number:Na 1794.3Removable Nut Manufacturer Part Number:Na 1794.3Platene StrovideI:Floating HolesThread Series:0.109 Inches MaximumRenovable Nut Manufacturer Part Number:Na 1794.3Na 100 Long Sharen Envolution:1.200 Long Sharen Envolution:Thread Series:0.109 InchesRenovable Nut Manufacturer Part Number:Na 100 Long Sharen Envolution:Naterial:Na 100 Long Sharen Envolution:Material:Na 100 Long Sharen Envolution:Naterial:Na 100 Golo NtMaterial:Inon Alloy Golo NtMaterial:Na 1552 Assi Std Single Material Response Nut Or Ams 557 Assi Std Single Material Response Nut Or Ams 557 Assi Std Single Material Response	Locking Feature:	Prevailing Torque All Metal Design
Nourting Hole Diameter:0.098 Inches Maximum And 0.103 Inches MaximumNut Selyie:PlateNut Height:0.948 Inches MaximumNut Height:0.438 Inches MaximumPlate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Witht:0.445 Inches MaximumRemovable Nut Manufacturer Code:0.250 Inches Minimum And 0.037 Inches MaximumNut Gourerbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Stalight HolesDistance From Aperture Center To Mounting Hole210 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Hole.086 Inches Minimum And 0.349 Inches MaximumCong Length:0.686 Inches Minimum And 0.690 Inches MaximumCong Length:.086 Inches Minimum And 0.690 Inches MaximumToread Series:0.19 Farear HolesRemovable Nut Manufacturer Part Number:Nas17942-34Thread Series:10.9 Fahrenheit MaximumThread Series:0.90 Inches Indimum And 0.690 Inches MaximumThread Series:0.910 InchesThread Series:0.910 InchesMaterial:10.910 InchesMaterial:10.930 Inches <trr>Material:</trr>	Counterbore Diameter:	0.194 Inches Nominal Nut
Nut Style:PiakeNut Length:0.948 Inches MaximumNut Height:0.948 Inches Maximum And 0.037 Inches MaximumPiake Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPiake Width:0.445 Inches Maximum And 0.037 Inches MaximumPiake Width:0.445 Inches Maximum And 0.037 Inches MaximumRemovable Nut Manufacturer Code:0.202 Inches Minimum And 0.037 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:1.406Center:0.391 Inches Minimum And 0.349 Inches MaximumCenter:0.866 Inches Minimum And 0.690 Inches MaximumCenter Dischare Between Mounting Hole.800 Enge Fannen MaximumCenter:0.917 Inches Maximum And 0.690 Inches MaximumThread Series:0.916 Fannen MaximumThread Series:0.916 Fannen MaximumThread Quantity Per Inch:3.20 Roce Marcine MaximumMaterial:Incol Mini Mounti Alepsonse Nut OrAms 5732 Assn Std Single Material Response Nut OrAms 5732	Lubrication:	Dry Film Lubricant
Nu Length:0.948 Inches MaximumNut Height:0.438 Inches MaximumPlate Mich0.438 Inches Maximum And 0.037 Inches MaximumPlate Width:0.445 Inches Maximum And 0.037 Inches MaximumRemovable Nut Manufacturer Code:0.445 Inches Maximum NutRemovable Nut Manufacturer Code:0.250 Inches Minimum NutNut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:106Distance From Aperture Center To Mounting Hole.339 Inches Minimum And 0.349 Inches MaximumRemovable Nut Manufacturer Part Number:Na1794:34Removable Nut Manufacturer Part Number:Na1794:34Toreng Asting:10.960 Inches MaximumToreng Asting:10.910 Inches MaximumThread Series:1.910 InchesParture Strovided:1.920 Inches MaximumThread Quantity Per Inch:3.2Material:Inclaling Goo NutMaterial:Inclaling Goo NutMaterial:Inclaling Straige Material Response NutMaterial:Inclaling Straige Material Response NutMaterial:Inclaling Material Response NutMaterial:Ins 552 Assn Std Single Material Response NutMaterial: </th <td>Mounting Hole Diameter:</td> <td>0.098 Inches Minimum And 0.103 Inches Maximum</td>	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height:0.438 Inches MaximumPlate Thickness:0.027 Inches Maximum And 0.037 Inches MaximumPlate Width:0.450 Inches Maximum And 0.037 Inches MaximumPlate Width:0.450 Inches Maximum And 0.037 Inches MaximumRemovable Nut Manufacture Ode:0.250 Inches Minimum NutNut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:1.4 IolesNut Mounting Provision:2.50 Inches Minimum And 0.349 Inches MaximumRemovable Nut Manufacture Path0.368 Inches Minimum And 0.399 Inches MaximumSenter To Center Distance Between Mounting Mot.368 Inches MaximumRemovable Nut Manufacture PathNas Index Maximum And 0.699 Inches MaximumRemovable Nut Manufacture PathNas Index Maximum And 0.699 Inches MaximumThread Series:Nas Index Maximum And 0.699 Inches MaximumThread Series:Nas Index MaximumThread Quarity Pa Inch:9.200 Endernenteit MaximumMaterial:InchesMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Maximum And 0.699 Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:Inches MaximumMaterial:MaximumMaterial:MaximumMate	Nut Style:	Plate
Plate Thickness:0.027 Inches Minimum And 0.037 Inches MaximumPlate Width:0.445 Inches MaximumRemovable Nut Manufacturer Code:8205Nut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.839 Inches Minimum And 0.349 Inches MaximumRemovable Nut Manufacturer Part Number:0.868 Inches Minimum And 0.590 Inches MaximumRemovable Nut Manufacturer Part Number:Nat 794C3-4Frem Rating:1.961 Counter DistanceThread Series:0.191 Inches MaximumMonting Hole Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Inon Alloy 660 NutMaterial:Inon Alloy 660 ShellMaterial:Sz52 Sasts Std Single Material Response NutMaterial Document And Classification:Ms 5525 Asst Std Single Material Response ShellKenter In Counter And Classification:Sz52 Sasts Std Single Material Response ShellKenter In Counter And Classification:Ms 552 Sasts Std Single Material Response Shell	Nut Length:	0.948 Inches Maximum
Plate Width:0.445 Inches MaximumRemovable Nut Manufacturer Code:80205Nut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Hole.686 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Na1794C34Thend Series:UnjfThread Series:UnjfRemovable Thread State:.030 Inches MaximumMonting Hore Inter State1.00 InchesMaterial:Inol Allo Géo NutMaterial:Inol Allo Géo ShellMaterial:Inol Allo Géo ShellMaterial:Ministoza State	Nut Height:	0.438 Inches Maximum
Removable Nut Manufacturer Code:80205Nut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Hole Along Length:0.866 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Na1794C3-4Menovable Nut Manufacturer Part Number:Na1794C3-4Temp Rating:450.0 Deg Fahrenheit MaximumThread Series:India NutMointing Hore Straice StraiceNa190 InchesMaterial:1.90 InchesMaterial:Inon Alloy G60 NutMaterial:Inon Alloy G60 NutMaterial:Nan Mice Of Strain Between Mounting Mole Strain Stat Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 573 Assn Std Single Material Response Sut O	Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Nut Counterbore Depth:0.250 Inches Minimum NutNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes0.686 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Nas1794C3-4Temp Rating:Nas1794C3-4Thread Series:UnjfFloating NutNaunter MutherThread Quantity Per Inch:32Nonlai Thread Size:0.190 Inches Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn 5732 Assn 5743 Single Material Response Nut Or Ams 5732 Assn 5743 Single Material Response Nut Or Ams 5732 Assn 57	Plate Width:	0.445 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:.339 Inches Minimum And 0.349 Inches MaximumDistance From Aperture Center To Mounting Hole Center:.399 Inches Minimum And 0.690 Inches MaximumCenter To Center Distance Between Mounting Hole Mole Length:.686 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Na1794C3-4Temp Rating:Na0.0 Eg Fahrenheit MaximumThread Series:UnifFeatures Provided:Floating NutThread Quantity Per Inch:32Nominal Thread Size:.109 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial:Non Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellSurface Treatment:Pasivate Overall	Removable Nut Manufacturer Code:	80205
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole center:339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Mong Length:0.868 Inches Minimum And 0.690 Inches MaximumCenter To Center Distance Between Mounting Mong Length:0.868 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Na1794C3-4Temp Rating:Viol Deg Fahrenheit MaximumThread Series:UnjfFatures Provide1:Ioating NutThread Quantity Per Inch:2Moninal Thread Size:0.190 InchesMaterial:Ion Alloy 660 NutMaterial:Ion Alloy 660 NutMaterial Pocument And Classification:Mis S252 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 525 Assn Std Single Material Response ShellMaterial Document And Classifi	Nut Counterbore Depth:	0.250 Inches Minimum Nut
Distance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Nas1794c3-4Temp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 NutMaterial Document And Classification:Ams 5525 Assn 5td Single Material Response Nut Or Ams 5732 Assn 5td Single Material Response NutSurface Treatment:Pasivate Overall	Nut Mounting Provision:	Straight Holes
Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Nas1794c3-4Temp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellSurface Treatment:Pasivate Overall	Mounting Hole Arrangement Style:	2 Holes
Along Length:0.686 Inches Minimum And 0.690 Inches MaximumRemovable Nut Manufacturer Part Number:Nas1794c3-4Temp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutSurface Treatment:Pasivate Overall		0.339 Inches Minimum And 0.349 Inches Maximum
Temp Rating:450.0 Deg Fahrenheit MaximumThread Series:UnjfFeatures Provided:Floating NutFread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Allog 660 NutMaterial:Iron Allog 60 ShellMaterial:Mis 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellSurface Treatment:Pasivate Overall	_	0.686 Inches Minimum And 0.690 Inches Maximum
Thread Series:UnifFeatures Provided:Foating NutThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShallMaterial:Iron Alloy 600 ShallMaterial Document And Classification:Mis 552 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 552 Assn Std Single Material Response NutMaterial Document And Classification:Ams 552 Assn Std Single Material Response NutMaterial Document And Classification:Ams 552 Assn Std Single Material Response NutMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Ams 552 Assn Std Single Material Response ShallMaterial Document And Classification:Material Response ShallMaterial Response ShallMaterial Response ShallMater	Removable Nut Manufacturer Part Number:	Nas1794c3-4
Features Provided:Floating NutFeatures Provided:Floating NutThread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellSurface Treatment:Pasivate Overall	Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Quantity Per Inch:32Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ms 5525 Assn Std Single Material Response Shell <th< th=""><th>Thread Series:</th><th>Unjf</th></th<>	Thread Series:	Unjf
Nominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response NutSurface Treatment:Passivate Overall	Features Provided:	Floating Nut
Material:Iron Alloy 660 NutMaterial:Iron Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response ShellSurface Treatment:Pasivate Overall	Thread Quantity Per Inch:	32
Material:Iron Alloy 660 ShellMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response NutSurface Treatment:Passivate Overall	Nominal Thread Size:	0.190 Inches
Material Document And Classification:Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response NutMaterial Document And Classification:Ams 5525 Assn Std Single Material Response NutSurface Treatment:Passivate Overall	Material:	Iron Alloy 660 Nut
Material Document And Classification: Assn Std Single Material Response Nut Material Document And Classification: Ams 5525 Assn Std Single Material Response Shell Surface Treatment: Passivate Overall	Material:	Iron Alloy 660 Shell
Surface Treatment: Passivate Overall	Material Document And Classification:	
	Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Treatment:	Passivate Overall
	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

Specification/standard Data:

80205-nas1791 Professional/industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C3-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.