

**Description**

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1791C34K
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-343-3186
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

# P/N NAS1791C3-4K Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.194 Inches Nominal Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.948 Inches Maximum
<b>Nut Height:</b>	0.438 Inches Maximum
<b>Plate Thickness:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Plate Width:</b>	0.445 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.250 Inches Nominal Nut
<b>Nut Mounting Provision:</b>	Dimpled Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.3398 Inches Minimum And 0.349 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.686 Inches Minimum And 0.690 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	Not Rated
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Iron Alloy 660 Nutiron Alloy 660 Seal
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nutams 5525 Assn Std Single Material Response Seal
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1791 Professional/industrial Association Standard

## How to Order

Order this plate - two lug locknut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1791C3-4K](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C3-4K) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.