

# P/N NAS1791C4-1

### **Description**

fine thread, floating nut, two holes, NAS1791 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: NAS1791C41

Minimum Qty (MOQ):

NSN: 5310-00-283-4618

Schedule B: 7318.16.0000

ECCN: EAR99

National Motor Freight: 013540, Alum Nuts









# **P/N NAS1791C4-1 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.286 Inches Maximum
Plate Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Plate Width:	0.574 Inches Nominal
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Shell
Material Document And Classification:	Ams5735 Assn Std Single Material Response Shell
Surface Treatment:	Passivate Shell
Specification/standard Data:	76301-st3-443 Manufacturers Standard

# **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C4-1">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS1791C4-1</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.