

Description

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1791C43
Minimum Qty (MOQ):	5
NSN:	5310-01-090-5559
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1791C4-3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Nominal Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.419 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.037 Inches Maximum
Plate Width:	0.547 Inches Maximum
Removable Nut Manufacturer Code:	80205
Nut Counterbore Depth:	0.188 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Removable Nut Manufacturer Part Number:	Nas1794c4-3
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Shell
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Shell
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C4-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.