# P/N NAS1791C4-4

## Description

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

| | |
|---|---|
| SKU / Model: | NAS1791C44 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-090-6367 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE AVAILABLE

* See page 2 for technical characteristics

# P/N NAS1791C4-4 Specifications

| | |
|---|---|
| **Thread Class:** | 3b |
| **Thread Direction:** | Right-hand |
| **Locking Feature:** | Prevailing Torque All Metal Design |
| **Counterbore Diameter:** | 0.254 Inches Nominal Nut |
| **Lubrication:** | Dry Film Lubricant |
| **Mounting Hole Diameter:** | 0.098 Inches Minimum And 0.103 Inches Maximum |
| **Nut Style:** | Plate |
| **Nut Length:** | 1.292 Inches Maximum |
| **Nut Height:** | 0.481 Inches Maximum |
| **Plate Thickness:** | 0.027 Inches Minimum And 0.037 Inches Maximum |
| **Plate Width:** | 0.547 Inches Maximum |
| **Removable Nut Manufacturer Code:** | 80205 |
| **Nut Counterbore Depth:** | 0.250 Inches Minimum Nut |
| **Nut Mounting Provision:** | Straight Holes |
| **Mounting Hole Arrangement Style:** | 2 Holes |
| **Distance From Aperture Center To Mounting Hole Center:** | 0.495 Inches Minimum And 0.505 Inches Maximum |
| **Center To Center Distance Between Mounting Holes Along Length:** | 0.998 Inches Minimum And 1.002 Inches Maximum |
| **Removable Nut Manufacturer Part Number:** | Nas1794c4-4 |
| **Temp Rating:** | 450.0 Deg Fahrenheit Maximum |
| **Thread Series:** | Unjf |
| **Features Provided:** | Floating Nut |
| **Thread Quantity Per Inch:** | 28 |
| **Nominal Thread Size:** | 0.250 Inches |
| **Material:** | Iron Alloy 660 Nut |
| **Material:** | Iron Alloy 660 Shell |
| **Material Document And Classification:** | Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nut |
| **Material Document And Classification:** | Ams 5525 Assn Std Single Material Response Shell |
| **Surface Treatment:** | Passivate Overall |
| **Surface Treatment Document And Classification:** | Qq-p-35 Fed Spec Single Treatment Response Overall |

| Specification/standard Data: | 80205-nas1791 Professional/industrial Association Standard |
|---|---|

# How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1791C4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.