

Description

NAS1792C4-1 Self-Locking Nutplate

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1792C41
Minimum Qty (MOQ):	5
NSN:	5310-01-050-7475
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

# P/N NAS1792C4-1 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.306 Inches Maximum
Nut Height:	0.246 Inches Maximum
Plate Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Plate Width:	0.554 Inches Nominal
Removable Nut Manufacturer Code:	76301
Nut Counterbore Depth:	0.070 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Removable Nut Manufacturer Part Number:	Stm445c4m1
Thread Series:	Unf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Base
Material:	Iron Alloy 660 Nut
Material Document And Classification:	Ams5525 Assn Std Single Material Response Mounting Or Ams5735 Assn Std Single Material Response Mounting
Surface Treatment:	Passivate Nut
Specification/standard Data:	76301-st3-442 Manufacturers Standard

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1792C4-1](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1792C4-1) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.