



Military-Fasteners.com

P/N NAS1801-04-11

Description

Fastener Length: 13/16", Thread: 4-40, Thread Length: 13/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18010411
Minimum Qty (MOQ):	25
NSN:	5305-01-364-3136
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1801-04-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.721 Inches Minimum And 0.818 Inches Maximum
Fastener Length:	0.771 Inches Minimum And 0.818 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.049 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.181 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340 And Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response And Mil-6049 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1801 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-04-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.