

P/N NAS1801-06-16

Description

length: 1", thread: 6-32, hex head screw, cruciform recess, full thread, alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS18010616

Minimum Qty (MOQ): 100

NSN: 5305-01-197-3553

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1801-06-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.920 Inches Minimum And 0.999 Inches Maximum
Fastener Length:	0.984 Inches Minimum And 1.031 Inches Maximum
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.093 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1801 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1801-06-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.