

Description

length: 1-3/8", thread: 8-32, hex head, cruciform recess, full thread, alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18010822
Minimum Qty (MOQ):	25
NSN:	5305-01-611-5002
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1801-08-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.327 Inches Minimum And 1.342 Inches Maximum
Fastener Length:	1.359 Inches Minimum And 1.406 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.1640 Inches
Document Type:	International Organization For Standardization
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Ams6382 Assn Std 1st Material Response Or Ams6415 Assn Std 2nd Material Response Or Ams6484 Assn Std 3rd Material Response Or Ams6325 Mil Spec 4th Material Response Or Ams6327 Assn Std 5th Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams-qq-p-416 Type Ii, Class 2 Assn Std Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1801-08-22 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-08-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.