

**Description**

length: 1-3/8", thread: 8-32, hex head, cruciform recess, full thread, alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS18010822                   |
| Minimum Qty (MOQ):      | 25                            |
| NSN:                    | 5305-01-611-5002              |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



## P/N NAS1801-08-22 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 1.327 Inches Minimum And 1.342 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 1.359 Inches Minimum And 1.406 Inches Maximum  |
| <b>Head Style:</b>  | Hexagon  |
| <b>Head Height:</b>   | 0.096 Inches Minimum And 0.110 Inches Maximum  |
| <b>Width Between Flats:</b>                                 | 0.243 Inches Minimum And 0.251 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type Ii   |
| <b>Nominal Thread Diameter:</b>                             | 0.1640 Inches  |
| <b>Document Type:</b>                                       | International Organization For Standardization   |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch  |
| <b>Screw Material:</b>                                      | Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740  |
| <b>Screw Material Document And Classification:</b>          | Ams6382 Assn Std 1st Material Response Or Ams6415 Assn Std 2nd Material Response Or Ams6484 Assn Std 3rd Material Response Or Ams6325 Mil Spec 4th Material Response Or Ams6327 Assn Std 5th Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium  |
| <b>Screw Surface Treatment Document And Classification:</b> | Ams-qq-p-416 Type Ii, Class 2 Assn Std Single Treatment Response   |
| <b>Thread Series Designator:</b>                            | Unjc   |
| <b>Specification/standard Data:</b>                         | 80205-nas1801-08-22 Professional/industrial Association Standard   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-08-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.