

## P/N NAS1801-3-21

### **Description**

thread: 10-32, hex head, cruciform recess, full thread, alloy steel, NAS1801 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1801321

Minimum Qty (MOQ): 50

NSN: 5305-01-098-6119

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1801-3-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.232 Inches Minimum And 1.311 Inches Maximum
Fastener Length:	1.296 Inches Minimum And 1.343 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340 Or Steel Comp E4340 Or Steel Comp 8740
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Type 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1801 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1801-3-21">https://military-fasteners.com/screws/machine+screws/NAS1801-3-21</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.