



★ FASTENERS

Military-Fasteners.com

P/N NAS1801-3-25

Description

length: 1-9/16", thread: 10-32, hex head screw, cruciform recess, full thread, alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1801325 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-348-0150 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1801-3-25 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.482 Inches Minimum And 1.561 Inches Maximum |
| Fastener Length: | 1.546 Inches Minimum And 1.593 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.314 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Steel Comp E4340 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1801 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-3-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.