

Description


Fastener Length: 1-13/32", Thread: 1/4-28, Thread Length: 1-23/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1801422
Minimum Qty (MOQ):	25
NSN:	5305-01-134-9363
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1801-4-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.295 Inches Minimum And 1.374 Inches Maximum
Fastener Length:	1.359 Inches Minimum And 1.406 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Part Name Assigned By Controlling Agency:	Navy Special Project
Screw Material:	Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1801 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-4-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.