

P/N NAS1801-4-7

Military-Fasteners.com

Description

length: 7/16", thread: 1/4-28, hex head screw, cruciform recess, full thread, alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS180147 |
|-------------------------|---|
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-189-7414 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1801-4-7 Specifications

| Thread Class: | 3a |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.287 Inches Minimum And 0.437 Inches Maximum |
| Fastener Length: | 0.422 Inches Minimum And 0.469 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Screw Material: | Steel Comp E4340 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6047 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2 Cl 2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1801 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1801-4-7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.