

P/N NAS1801-4D11

Description

Fastener Length: 11/16", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS18014D11

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-527-7192



^{*} See page 2 for technical characteristics

P/N NAS1801-4D11 Specifications

| Thread Class: | 3a |
|---|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.688 Inches Nominal |
| Fastener Length: | 0.700 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.046 Inches Minimum |
| Internal Drive Style: | Cross Recess Type Ii |
| Nominal Thread Diameter: | 0.250 Inches |
| Hole Quantity: | 3 |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 4340 |
| Screw Surface Treatment: | Cadmium |
| Head Hole Configuration Style: | Hexagon Corners |
| Bearing Surface Of Head Surface Finish: | 63.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1801-4D11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.