

Description

Fastener Length: 11/16", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18014D11
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-527-7192

NO IMAGE
AVAILABLE

P/N NAS1801-4D11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Nominal
Fastener Length:	0.700 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	3
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340
Screw Surface Treatment:	Cadmium
Head Hole Configuration Style:	Hexagon Corners
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-4D11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.