

**Description**

NAS1801 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS18014D13      |
| Minimum Qty (MOQ): | 10               |
| NSN:               | 5305-01-623-3945 |



\* See page 2 for technical characteristics

## P/N NAS1801-4D13 Specifications

|                                                             |                                                                                                                                                      |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                        | 3a                                                                                                                                                   |
| <b>Thread Direction:</b>                                    | Right-hand                                                                                                                                           |
| <b>Thread Length:</b>                                       | 0.7965 Inches Minimum And 0.8435 Inches Maximum                                                                                                      |
| <b>Fastener Length:</b>                                     | 0.7965 Inches Minimum And 0.8435 Inches Maximum                                                                                                      |
| <b>Head Style:</b>                                          | Hexagon                                                                                                                                              |
| <b>Head Height:</b>                                         | 0.125 Inches Minimum And 0.140 Inches Maximum                                                                                                        |
| <b>Width Between Flats:</b>                                 | 0.367 Inches Minimum And 0.376 Inches Maximum                                                                                                        |
| <b>Hole Diameter:</b>                                       | 0.046 Inches Minimum And 0.056 Inches Maximum                                                                                                        |
| <b>Internal Drive Style:</b>                                | Cross Recess Type li                                                                                                                                 |
| <b>Nominal Thread Diameter:</b>                             | 0.2500 Inches                                                                                                                                        |
| <b>Hole Quantity:</b>                                       | 3                                                                                                                                                    |
| <b>Thread Quantity Per Inch:</b>                            | 28                                                                                                                                                   |
| <b>Part Name Assigned By Controlling Agency:</b>            | Screw,hex Head,cruciform Recess,full Thread,alloy Steel,160ksi FtU                                                                                   |
| <b>Screw Material:</b>                                      | Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740                                                                                                |
| <b>Screw Material Document And Classification:</b>          | Ams6382 National Spec 1st Material Response Or Ams6415 Or Ams6484 National Spec 2nd Material Response Or Ams6322 National Spec 3rd Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium                                                                                                                                              |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,type li,class 2 Fed Spec Single Treatment Response                                                                                          |
| <b>Head Hole Configuration Style:</b>                       | Hexagon Flats                                                                                                                                        |
| <b>Bearing Surface Of Head Surface Finish:</b>              | 63.0 Microinches                                                                                                                                     |
| <b>Shank Surface Finish:</b>                                | 32.0 Microinches                                                                                                                                     |
| <b>Thread Surface Finish:</b>                               | 32.0 Microinches                                                                                                                                     |
| <b>Thread Series Designator:</b>                            | Unjf                                                                                                                                                 |
| <b>Specification/standard Data:</b>                         | 80205-nas1801 Professional/industrial Association Standard                                                                                           |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-4D13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.