

**Description**

NAS1801 series screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS18014D13
Minimum Qty (MOQ):	10
NSN:	5305-01-623-3945



## P/N NAS1801-4D13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.7965 Inches Minimum And 0.8435 Inches Maximum
<b>Fastener Length:</b>	0.7965 Inches Minimum And 0.8435 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Minimum And 0.056 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type li
<b>Nominal Thread Diameter:</b>	0.2500 Inches
<b>Hole Quantity:</b>	3
<b>Thread Quantity Per Inch:</b>	28
<b>Part Name Assigned By Controlling Agency:</b>	Screw,hex Head,cruciform Recess,full Thread,alloy Steel,160ksi FtU
<b>Screw Material:</b>	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Ams6382 National Spec 1st Material Response Or Ams6415 Or Ams6484 National Spec 2nd Material Response Or Ams6322 National Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type li,class 2 Fed Spec Single Treatment Response
<b>Head Hole Configuration Style:</b>	Hexagon Flats
<b>Bearing Surface Of Head Surface Finish:</b>	63.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1801 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-4D13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.