


Description

NAS1801 series screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS18014D13
Minimum Qty (MOQ):	10
NSN:	5305-01-623-3945



P/N NAS1801-4D13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.7965 Inches Minimum And 0.8435 Inches Maximum
Fastener Length:	0.7965 Inches Minimum And 0.8435 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.2500 Inches
Hole Quantity:	3
Thread Quantity Per Inch:	28
Part Name Assigned By Controlling Agency:	Screw,hex Head,cruciform Recess,full Thread,alloy Steel,160ksi FtU
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Ams6382 National Spec 1st Material Response Or Ams6415 Or Ams6484 National Spec 2nd Material Response Or Ams6322 National Spec 3rd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,type li,class 2 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Hexagon Flats
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1801 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-4D13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.