

## Description

Fastener Length: 25/32", Thread: 3/8-24, Thread Length: 25/32", hex head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1801612
Minimum Qty (MOQ):	20
NSN:	5305-01-309-6540
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1801-6-12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.651 Inches Minimum And 0.781 Inches Maximum
<b>Fastener Length:</b>	0.734 Inches Minimum And 0.781 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.552 Inches Minimum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp E4340 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response
<b>Bearing Surface Of Head Surface Finish:</b>	63.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1801 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1801-6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.