

## P/N NAS1801-6-16

### **Description**

Fastener Length: 63/64", Thread: 3/8-24, Thread Length: 63/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1801616
Minimum Qty (MOQ):	10
NSN:	5305-01-229-5543
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1801-6-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.968 Inches Minimum And 1.064 Inches Maximum
Fastener Length:	0.984 Inches Minimum And 1.064 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.3750 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Or Ams6322 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1801 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1801-6-16">https://military-fasteners.com/screws/machine+screws/NAS1801-6-16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.