

**Description**

Fastener Length: 9/32", Thread: 4-40, Thread Length: 13/64", NAS1802 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1802044
Minimum Qty (MOQ):	50
NSN:	5305-01-229-5546
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1802-04-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.217 Inches Minimum And 0.218 Inches Maximum
<b>Fastener Length:</b>	0.234 Inches Minimum And 0.281 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.049 Inches Minimum And 0.060 Inches Maximum
<b>Width Between Flats:</b>	0.181 Inches Minimum And 0.189 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1802 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-04-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.