

Description

Fastener Length: 21/64", Thread: 4-40, Thread Length: 21/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1802045
Minimum Qty (MOQ):	25
NSN:	5305-01-182-8349
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1802-04-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.246 Inches Minimum And 0.343 Inches Maximum
Fastener Length:	0.296 Inches Minimum And 0.343 Inches Maximum
Head Style:	Hexagon
Head Height:	0.049 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.181 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams A5737 Assn Std Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-04-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.