

P/N NAS1802-06-10P

Military-Fasteners.com

Description

Fastener Length: 21/32", Thread: 6-32, Thread Length: 37/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS18020610P
Minimum Qty (MOQ):	5
NSN:	5305-01-527-2204



P/N NAS1802-06-10P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.561 Inches Minimum And 0.593 Inches Maximum
Fastener Length:	0.609 Inches Minimum And 0.656 Inches Maximum
Head Style:	Hexagon
Head Height:	0.052 Inches Minimum And 0.075 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Rq-4a Global Hawk
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Machine
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-418,type li Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1802-06-10P</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.