

## P/N NAS1802-06-10P

## **Description**

Fastener Length: 21/32", Thread: 6-32, Thread Length: 37/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:

Minimum Qty (MOQ):

5

NSN: 5305-01-527-2204



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1802-06-10P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.561 Inches Minimum And 0.593 Inches Maximum
Fastener Length:	0.609 Inches Minimum And 0.656 Inches Maximum
Head Style:	Hexagon
Head Height:	0.052 Inches Minimum And 0.075 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Rq-4a Global Hawk
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Machine
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-418,type Ii Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1802-06-10P">https://military-fasteners.com/screws/machine+screws/NAS1802-06-10P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.