

Description

Fastener Length: 1-5/64", Thread: 6-32, Thread Length: 1-1/64", hex head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18020617
Minimum Qty (MOQ):	20
NSN:	5305-01-567-8062
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1802-06-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.013 Inches Minimum And 1.028 Inches Maximum
Fastener Length:	1.045 Inches Minimum And 1.092 Inches Maximum
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.093 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-315 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-06-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.