

Description

Fastener Length: 1-9/32", Thread: 6-32, Thread Length: 1-9/32", NAS1802 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS18020620
Minimum Qty (MOQ):	20
NSN:	5305-01-494-3849
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1802-06-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.234 Inches Minimum And 1.281 Inches Maximum
Fastener Length:	1.234 Inches Minimum And 1.281 Inches Maximum
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.093 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.1380 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-06-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.