

Description

Fastener Length: 2-5/32", Thread: 6-32, Thread Length: 1-3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS18020634
Minimum Qty (MOQ):	5
NSN:	5305-01-347-5151
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



NO IMAGE
AVAILABLE

P/N NAS1802-06-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Nominal
Fastener Length:	2.109 Inches Minimum And 2.156 Inches Maximum
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.093 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-06-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.