

Description


Fastener Length: 9/32", Thread: 6-32, Thread Length: 9/32", NAS1802 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802064
Minimum Qty (MOQ):	20
NSN:	5305-01-348-8655
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1802-06-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.172 Inches Minimum And 0.281 Inches Maximum
Fastener Length:	0.234 Inches Minimum And 0.281 Inches Maximum
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.093 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-06-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.