

Description

Fastener Length: 37/64", Thread: 6-32, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802069P
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-513-4758



* See page 2 for technical characteristics

P/N NAS1802-06-9P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.515 Inches Minimum And 0.530 Inches Maximum
Fastener Length:	0.546 Inches Minimum And 0.593 Inches Maximum
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.093 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5853 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Ty Ii, Cl 2 Fed Spec Single Treatment Response
Special Features:	Hydrogen Embrittlement Baking And Testing Per Qq-p-416 Are Not Required For A286 Material
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-06-9P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.