



Military-Fasteners.com

P/N NAS1802-08-17

Description

Fastener Length: 1-11/64", Thread: 8-32, Thread Length: 63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS18020817      |
| Minimum Qty (MOQ): | 30 EA            |
| NSN:               | 5305-01-612-8003 |
| Schedule B:        | 7318.15.6080     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N NAS1802-08-17 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.960 Inches Minimum And 0.992 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 1.159 Inches Minimum And 1.173 Inches Maximum  |
| <b>Head Style:</b>  | Hexagon  |
| <b>Head Height:</b>   | 0.096 Inches Minimum And 0.110 Inches Maximum  |
| <b>Width Between Flats:</b>                                 | 0.243 Inches Minimum And 0.251 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch  |
| <b>Screw Material:</b>                                      | Steel Corrosion Resisting  |
| <b>Screw Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response Or Ams 5853 Assn Std Single Material Response |
| <b>Screw Surface Treatment:</b>                             | Passivate  |
| <b>Screw Surface Treatment Document And Classification:</b> | -qq-p-35 Fed Spec Single Treatment Response  |
| <b>Bearing Surface Of Head Surface Finish:</b>              | 63.0 Microinches   |
| <b>Shank Surface Finish:</b>                                | 32.0 Microinches   |
| <b>Thread Surface Finish:</b>                               | 32.0 Microinches   |
| <b>Thread Series Designator:</b>                            | Unjc   |
| <b>Specification/standard Data:</b>                         | 80205-nas1802 Professional/industrial Association Standard   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-08-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.