

Description

Fastener Length: 1-17/64", Thread: 8-32, Thread Length: 1-15/64", NAS1802 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS18020820 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-01-305-6308 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



P/N NAS1802-08-20 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.116 Inches Minimum And 1.239 Inches Maximum |
| Fastener Length: | 1.224 Inches Minimum And 1.271 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.141 Inches Minimum And 0.164 Inches Maximum |
| Width Between Flats: | 0.243 Inches Minimum And 0.251 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Bearing Surface Of Head Surface Finish: | 63.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1802 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-08-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.