

Description

Fastener Length: 1-25/32", Thread: 8-32, Thread Length: 1-45/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS18020828
Minimum Qty (MOQ):	10
NSN:	5305-01-527-0410
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1802-08-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.686 Inches Minimum And 1.718 Inches Maximum
Fastener Length:	1.734 Inches Minimum And 1.781 Inches Maximum
Head Style:	Hexagon
Head Height:	0.067 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Rq-4a Global Hawk
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Machine
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-08-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.