

Description

length: 7/16", thread: 8-32, hex head, cruciform recess, full thread, corrosion resistant steel, NAS1802 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802087
Minimum Qty (MOQ):	25
NSN:	5305-01-130-8380
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1802-08-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.357 Inches Minimum And 0.436 Inches Maximum
Fastener Length:	0.421 Inches Minimum And 0.468 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1802 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-08-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.