

Description

Fastener Length: 11/16", Thread: 8-32, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802088P
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-508-2102
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1802-08-8P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.484 Inches Minimum And 0.531 Inches Maximum
Fastener Length:	0.641 Inches Minimum And 0.692 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Cross Recess Type II
End Item Identification:	Rq-4a
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw Hex Head Cruciform Recess, Full Thread, Alloy Steel, 160,000 Psi Tensile
Screw Material:	Steel Comp 4340
Screw Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Ty 11, Cl 2 Fed Spec Single Treatment Response
Special Features:	Drive Style Cruciform Recess 2 Per Ms9006
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-08-8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.