

Description

Fastener Length: 49/64", Thread: 10-32, Thread Length: 39/64", NAS1802 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1802310P
Minimum Qty (MOQ):	25
NSN:	5305-01-530-2484
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



P/N NAS1802-3-10P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.545 Inches Minimum And 0.624 Inches Maximum
Fastener Length:	0.714 Inches Minimum And 0.776 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1802-3-10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.